



## Features

- ✓ Intel® Alder Lake-N N100 3.4Ghz/N200 3.7Ghz Platform
- ✓ 14" 1080P Full HD Display
- ✓ Multi languages isolated keyboard
- ✓ Support up to 4K@60Hz resolution for connected display
- ✓ Support USB type-C including DP Power Delivery in.
- ✓ Intel® PTT for system without Hardware TPM
- ✓ Stylish design with metal chassis
- ✓ All designed for Cloud & VDI solutions, VMware, Microsoft and Citrix

## N14111 Specification



Processor System	Intel® Alder Lake-N N100 (0.8Ghz – 3.4Ghz, DD5-4800MHz, TDP: 6W)
	Intel® Alder Lake-N N200 (1.0Ghz – 3.7Ghz, DD5-4800MHz, TDP: 6W)
	Intel® Gemini Lake Express Chipset
Display	14" Full HD (1920x1080) 16:9 panel, 3.0mm
Memory	1 x SODIMM DDR4 3200MHz, expandable up to 16GB
Video Controller	Intel® UHD Graphics
Storage	Factory Option: 1 x M.2 2280 SSD, PCIe Gen 3 interface
Audio	High-Definition Audio with built-in array microphone and speaker
Keyboard	Multi languages isolated keyboard
	Built-in Click pad with Microsoft PTP multi-gesture and scrolling function
I/O Interface Options	2 x USB 2.0 port (Type A)
	1 x USB 3.2 Gen1 port (Type A)
	1 x USB 3.2 Gen 1 port (Type C)
	1 x HDMI™ output port (with HDCP)
	1 x 2-in-1 Audio Combo jack (headphone + microphone)
	1 x DC-in jack
Card Reader	1 x PD-in Type-C
Slot	MicroSD Card reader
	Two M.2 card slots <ul style="list-style-type: none"> <li>- 1<sup>st</sup> for WLAN Combo M.2 2230 Card with PCIe/USB/CNVi interface (E key)</li> <li>- 2<sup>nd</sup> for M.2 2280 SSD Card with PCIe Gen3x4 interface (Mkey)</li> </ul>
Communication	Intel® Dual Band WiFi 6E AX21 2x2 AX + BT CNVi M.2 2230 1.0M HD video camera, optional 2.0M FHD camera with TNR
Power Supply	Full range AC adapter, AC in 100-240V, 50~60Hz, DC output 19V 2.37A, 45W Embedded Polymer Smart Lithium-Ion battery pack, 36WH
Security	Security Lock Slot (Kensington Type) Intel® PTT for system without hardware TPM
OS Support	Windows® 11 (64bit)